

The Type I tagline reel is made of a high-impact Lexan plastic casing and holds up to 600 feet (180 m) of 1/16-inch (0.16 cm) Kevlar braided tagline. The reel has a handle in which a 1/2- inch (1.27 cm) diameter bank stake may be inserted to support the reel on the stream bank while in use. A variable drag device and lock-down bolt also are features of this reel. The standard reel is supplied with 400 feet of wading Kevlar tagline.

The USGS Kevlar tagline consist of a Kevlar inner core enclosed in a nylon jacket and dyed yellow with black marks for improved visibility. The Kevlar wading tagline is 1/16-inch (0.16 cm) diameter and floats for ease of operation such as hanging up in brush or rocks. The Kevlar tagline is waxed with a commercial thread wax. This tagline can be rewaxed as needed with Rewaxer cleaner pad to keep it clean, preserve its abrasion resistance, and assure that the line will float.



Product Features

- Comes in English or Metric units
- Lengths up to 600ft or 180m
- Tagline break strength of 1,700 lbs(771 kg)

TAGLINE MARKING CHART	
Measurement Unit	Marking Interval
English	2, 10, 100 ft.
Metric	1, 5, 50 m

ORDERING INFORMATION

- [109-018](#) Tagline, Kevlar, HIF Reel, 200ft
- [109-019](#) Tagline, Kevlar, HIF Reel, 300ft
- [109-020](#) Tagline, Kevlar, HIF Reel, 400ft
- [109-021](#) Tagline, Kevlar, HIF Reel, 600ft
- [109-022-1](#) Tagline, Kevlar, HIF Reel, 60m
- [109-022-2](#) Tagline, Kevlar, HIF Reel, 120m
- [109-022-3](#) Tagline, Kevlar, HIF Reel, 180m
- [109-025](#) Bank Stank
- [109-054](#) Rewaxer Cleaner Pad